

Screen 3

Three-way bi-amp system

cinema

features

- ▶ Three-way design
- ▶ Very low distortion mid-range
- ▶ Very shallow profile
- ▶ 90° x 40° dispersion

applications

- ▶ Behind screen placement
- ▶ Medium scale cinemas
- ▶ Post production suites


The Screen 3 is a 3-way system, with dedicated mid-range and high frequency sections. Developed to meet the requirements of small to medium size screening rooms and post production suites that require the mid-range definition and intelligibility not achievable with a traditional 2-way system.



technical specifications

TYPE	Three-way bi-amp screen system
FREQUENCY RESPONSE (1)	45Hz-20kHz \pm 3dB
DRIVERS	15" (380mm) bass driver 6.5" (165mm) mid driver 1" (25mm) exit compression driver
RATED POWER (2)	LF: 550W AES, 2200W peak MF + HF: 150W AES, 600W peak
SENSITIVITY (3)	LF: 98dB MF + HF: 106dB
NOMINAL IMPEDANCE	LF: 8 ohms MF + HF: 16 ohms
DISPERSION (-6dB)	90° horizontal, 40° vertical
CROSSOVER	630Hz active, 3kHz passive
ENCLOSURE	Vented
FINISH	Matt black
CONNECTORS	Binding Posts
DIMENSIONS	LF: (W) 650mm x (H) 765mm x (D) 307mm (W) 26ins x (H) 30ins x (D) 12ins MF/HF: (W) 490mm x (H) 385mm x (D) 290mm (W) 19.3ins x (H) 15.1ins x (D) 11.4ins
WEIGHT	LF: 39kg (86lbs) MF/HF: 9kg (19.8lbs)

overall dimensions



SCREEN_3

Century Point, Halifax Road, Cressex Business Park,
High Wycombe, Buckinghamshire HP12 3SL, England.
Telephone: +44 (0)1494 535312 Facsimile: +44 (0)1494 438669
E-mail: info@martin-audio.com
All information is Copyright © 2003 Martin Audio Ltd.



www.martin-audio.com

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>