

Attix 12 AS/PE EC Critical Applications Vacuum



The Attix 12 AS/PE EC vacuum is powered by a spark less, brush less, electronically-controlled motor. No spark means it is suitable for use in hazardous areas where ignition sources are prohibited.

Features

- No carbon particles from motor brushes in the vacuum exhaust
- Ambient air is filtered before passing through motor-cooling duct
- SoftStart motor prevents power peaks and voltage breakdowns, extending service life up to 10 times as long as conventional motor
- Designed for use with pneumatic or electric power tools
 - AutoStart circuitry allows vacuum power to be remotely controlled by the operator from the connected tool
 - Anti-static hose



Includes:

- Washable, one-micron fleece filter
- 1 1/4" x 16' anti-static suction hose
- Lockable containment bag
- Auxiliary electrical outlet (110 Volt)



Technical Data:

- 57 dB(A) sound level
 - 1.6 HP motor
 - 140 CFM (air flow)
- 105" static water lift
 - 53 lbs

Nilfisk-ALTO Cleaning Systems, Inc.
2100 Highway 265 South
Springdale, AR 72764
877.366.2586 - Phone
800.405.9092 - Fax



**Nilfisk
ALTO**

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>